



**RTAPE GRAPHIC TAPES**

## The NEW, universal clear application tape for maximum versatility & precision

Clear Choice® is an ultra-clear, application tape that provides exceptional performance and versatility for the widest range of sign applications.

### **AT60n** Low Tack

A Low Tack film for transferring large cut graphics and protecting digital prints.

### **AT65** High Tack

Universal high tack film for transferring small and fine detail cut graphics and vinyl films with tight release liners.

### **AT75.1** High Tack

Embossed surface film ideal for small to medium size cut graphics, with air-egress micro channels for bubble-free lamination of tape to film.

### *New!* **Product Improvements**

- Enhanced Adhesion
- Improved release liner adhesion with Conform characteristics
- Improvements to lifting and transferring graphics
- No adhesive residue with wet applications
- No water whitening upon contact with water/solution

#### **Applications**

- Textured and matte finish vinyl films
- Fine lettering
- Textured wrap, window and wall films
- Thermal die cuts

#### **Product Information**

- Clear film
- Repositionable
- Easy handling and removal
- No milky residue and water whitening when used for wet applications

#### **AT60n and AT65**

Emboss/Finish:  
Fine Texture for easy release/  
unwind and installation

#### **AT75.1**

Emboss/Finish:  
Heavy Surface Texture with  
Air Egress Micro tunnels

AT75.1 vs AT60n ▼ See the difference!



Printed on Digital Coated 80# cover on a Ricoh C751EX

## TECHNICAL DATA ▶

### Physical Properties

**Color** Transparent  
**Shelf Life** 1 year

	AT60n	AT65	AT75.1
<b>Color</b>	Transparent	Transparent	Transparent
<b>Adhesive</b>	Acrylic	Acrylic	Modified polyacrylate
<b>Caliper</b>	Embossed Polypropylene	Embossed Polypropylene	Embossed HOPE
	3.7 mil (93 μ)	3.7 mil (93.7 μ)	4.25 mil (106.4 μ)
<b>Tack Level</b>	Low	High	High
<b>Adhesion to Steel*</b>	1-4 N/100 mm (1-3 oz.)	2.1-6.5 N/100 mm (2 - 6 oz.)	2.1 N/25 mm (7.5 oz.)
<b>Die-Cut Graphics Size</b>	Large	Small-Med	Small-Med
<b>Wet Application Installation</b>	Good	Excellent	Excellent
<b>Compatible Vinyl</b>	Gloss/Smooth	Gloss/Smooth	Gloss/Smooth and Matte/Textured Vinyl
<b>Tensile</b>	25 MPa (3600 psi)	25 MPa (3600 psi)	13 MPa (2000 psi)
<b>Elongation</b>	750%	750%	300-500%

\* TEST METHOD: PSTC-101

**WARRANTY** Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. Nekoosa will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.